


VP-720DS

ProScale 7 - Seamless Switcher/Scaler



The Kramer **VP-720DS** is a true multi-standard video to RGBHV scaler that converts video, s-Video, component video (SDTV and HDTV), VGA-through-UXGA, and DVI-D signals to ten user-selectable pixel rates: VGA (640 x 480), SVGA (800 x 600), XGA (1024 x 768), SXGA (1280 x 1024), UXGA (1600 x 1200), 1024 x 852, 1024 x 1024, 1366 x 768, 1365 x 1024 and 1280 x 720. The machine also acts as 7-input Seamless Presentation switcher. It digitally reprocesses the signal to correct mastering errors, and regenerate the video at a higher line and pixel rate format, providing native-resolution video for LCD, DLP and Plasma displays. The **VP-720DS** allows scaling of any graphics resolution to any other resolution (scaling for example, a VGA input to an UXGA output, or an SXGA input to an SVGA output, etc). The machine incorporates a unique graphics-scaling engine with image enhancement algorithms, which are built into the firmware. The **VP-720DS** is specifically designed to improve video quality by reducing Chroma noise. On top of that, it includes a built in Picture-in-Picture inserter, allowing the insertion of any video source into a graphics background and vice versa, as well as allowing the inserted image to be sized and positioned anywhere on the screen. In addition, the PIP can display a Split-Screen (2 images side by side). Audio channels are switched in audio-follow-video mode. The units can be controlled via front panel touch keys, Infra Red remote control, and RS-232. It features a user-friendly on-screen display for making the adjustments. The **VP-720DS** incorporates a full scale ProcAmp for video and audio correction and enhancement, and offer 3:2/2:2 pull down. It is housed in a 19" 1U, rack-mountable metal enclosure and use a universal 100-240VAC automatic power supply.



TECHNICAL SPECIFICATIONS

INPUT:	2 x CV 1Vpp/75Ω on RCAs; 2 x YC, Y = 1Vpp/75Ω C = 0.3Vpp/75Ω on 4p connectors; 1 x component (Y, Pb/Cb, Pr/Cr - both progressive and interlaced signals accepted) on RCAs; 1 x DVI-D; 1x VGA on HD 15 connector (VGA through UXGA). 3x audio stereo on RCAs, 1 x PC audio on 3.5mm mini connector.
OUTPUTS:	1 x RGBHV (VGA Format) on HD15 connector; One line-level stereo audio on RCAs.
OUTPUT RESOLUTIONS:	VGA (640 x 480), SVGA (800 x 600), XGA (1024 x 768), SXGA (1280 x 1024), UXGA (1600 x 1200), 1024 x 852, 1024 x 1024, 1366 x 768, 1365 x 1024 and 1280 x 720, as well as a use-definable output resolution.
CONTROL:	Front panel touch switches, IR remote control, both with OSD. RS-232 on a DB-9 connector. Picture-In-Picture: Video in Graphics (or vice versa) in sizes up to quarter screen at any location, or Split Screen (2 images side-by-side).
ADDITIONAL CONTROLS:	Freeze, zoom, different selectable vertical refresh rates, ProcAmp control, output image scaling and aspect ratio change.
POWER SOURCE:	100-240 VAC, 50/60Hz, 30 VA.
DIMENSIONS:	19" (W), 9.3" (D) 1 RU height.
ACCESSORIES:	IR remote control, power cord.
WEIGHT:	3kg (6.6lbs) approx.

TYPICAL APPLICATIONS

- Projection systems in conference rooms, board rooms, auditoriums, hotels, churches.
- Any application where high quality conversion and switching of multiple and different video signals to graphical data signals is required for projection purposes.

